SCHILTZ handling

wh-010109-nl



STEEKKAR VOOR APPARATEN OF ROLLEN

Art. BR.14... / 16...

Push and carry trucks

- Load capacity 350 kg
- For transport of heavy, bulky goods and products sensitive to shock such as big household appliances
- Foot plate with rubber covering
- Protective covering on frame
- Steel tube, plastic coated, RAL 5010
- 2 versions of height available

Wheels:

Solid rubber with red plastic rim, 250 Ø x 60 mm, roller bearings pneumatic tyres with steel sheet rim 260 Ø x 85 mm, roller bearings

Extras:

Carrying bars

Can be used as single or pair. Holding device for the bars at the truck.



Ref.-No. BR.1451.9



Push and carry truck 1100

Load capacity:	35
Wheels	solid rubber
Overall height/width	1100/550 mm
Frame width	400 mm
Foot plate dim.	400 x 190 mm
Weight	18,6 kg
RefNo.	BR.1461.3

pneum. tyres 1100/570 mm 400 mm 400 x 190 mm 16,8 kg **BR.1461.6**
 Load capacity:
 35

 Wheels
 solid rubber

 Overall height/width
 1300/550 mm

 Frame width
 400 mm

 Foot plate dim.
 400 x 190 mm

 Weight
 19 kg

 Ref.-No.
 BR.1451.3

Push and carry truck 1300

350 kg

pneum. tyres 1300/570 mm 400 mm 400 x 190 mm 17,2 kg **BR.1451.6**

Beam trucks

- For various cylinders and other round objects standing upright or for easy horizontal transport of all kind of round objects with various diameters
- Steel tube, plastic coated, RAL 5010

Wheels BR.1412.5 and .6:

Solid rubber with red plastic rim, 250 Ø x 60 mm, roller bearings pneumatic tyres with steel sheet rim 260 Ø x 85 mm, roller bearings

Wheels BR.1635.5 and .6:

Solid rubber with steel sheet rim, 400 Ø x 75 mm, roller bearings pneumatic tyres with steel sheet rim 400 Ø x 100 mm, roller bearings





Beam truck

Load capacity:	350 kg	
Wheels	solid rubber	pneum. tyres
Overall height/width	1100/490 mm	1100/505 mm
Frame width	300 mm	300 mm
Foot plate dim.	300 x 170 mm	300 x 170 mm
Weight	17 kg	15 kg
RefNo.	BR.1412.3	BR.1412.6

Beam truck

Load capacity:	400 kg	
Wheels	solid rubber	pneum. tyres
Overall lenght	1575 mm	1575 mm
Overall width	620 mm	620 mm
Area of support	1575 x 510 mm	1575x510 mm
Weight	22 kg	15 kg
RefNo.	BR.1635.5	BR.1635.6